

TUBOS PADRÃO SCHEDULE DE AÇO INOX NAS NORMAS ASTM A312, A409, A778 CONFORME ANSI B36.10 E B36.19																
DN	pol.	externo	SCH 5s		SCH 10s		SCH 20s		SCH 40s		SCH 80s		SCH 160s		SCH XXS	
			Parede	Peso Kg/m	Parede	Peso Kg/m	Parede	Peso Kg/m	Parede	Peso Kg/m	Parede	Peso Kg/m	Parede	Peso Kg/m	Parede	Peso Kg/m
6	1/8"	10,29	*	*	1,24	0,281	1,5	0,32	1,73	0,371	2,41	0,475	*	*	*	*
8	1/4"	13,72	*	*	1,65	0,498	2	0,58	2,24	0,644	3,02	0,809	*	*	*	*
10	3/8"	17,15	*	*	1,65	0,64	2	0,75	2,31	0,858	3,2	1,117	*	*	*	*
15	1/2"	21,34	1,65	0,813	2,11	1,016	2,5	1,16	2,77	1,288	3,73	1,647	4,78	1,981	7,47	2,59
20	3/4"	26,67	1,65	1,033	2,11	1,297	2,5	1,49	2,87	1,71	3,91	2,227	5,56	2,938	7,82	3,69
25	1"	33,4	1,65	1,311	2,77	2,124	3	2,25	3,38	2,54	4,55	3,286	6,35	4,299	9,09	5,531
32	1.1/4"	42,16	1,65	1,673	2,77	2,731	3	2,89	3,56	3,44	4,85	4,529	6,35	5,692	9,7	7,881
40	1.1/2"	48,26	1,65	1,925	2,77	3,154	3	3,35	3,68	4,106	5,08	5,49	7,14	7,349	10,16	9,689
50	2"	60,33	1,65	2,423	2,77	3,991	3,5	4,9	3,91	5,522	5,54	7,598	8,74	11,286	11,07	13,649
65	2.1/2"	73,03	2,11	3,746	3,05	5,342	3,5	6	5,16	8,766	7,01	11,584	9,53	15,147	14,02	20,71
80	3"	88,9	2,11	4,584	3,05	6,554	4	8,5	5,49	11,462	7,62	15,502	11,13	21,665	15,24	28,098
90	3.1/2"	101,6	2,11	5,254	3,05	7,523	4	9,772	5,74	13,772	8,08	18,914	*	*	*	*
100	4"	114,3	2,11	5,925	3,05	8,493	4	11,043	6,02	16,316	8,56	22,656	13,49	34,039	17,12	41,66
125	5"	141,3	2,77	9,605	3,4	11,736	5	17,06	6,55	22,092	9,53	31,432	15,88	49,851	19,05	58,31
150	6"	168,28	2,77	11,475	3,4	14,032	5	20,434	7,11	28,682	10,97	43,194	18,26	68,566	21,95	80,43
200	8"	219,08	2,77	14,997	3,76	20,264	6,5	34,586	8,18	43,181	12,7	65,604	23,01	112,92	22,22	109,57
250	10"	273,05	3,4	22,948	4,19	28,197	6,5	43,366	9,27	61,204	12,7	82,79	28,58	174,9	25,4	157,51
300	12"	323,85	3,96	31,707	4,57	36,522	6,5	51,631	9,53	74,977	12,7	98,95	33,32	242,53	25,4	189,81
350	14"	355,6	3,96	34,854	4,78	41,973	*	*	*	*	*	*	*	*	*	*
400	16"	406,4	4,19	42,182	4,78	48,051	*	*	*	*	*	*	*	*	*	*
450	18"	457,2	4,19	47,5	4,78	54,129	*	*	*	*	*	*	*	*	*	*
500	20"	508	4,78	60,2	5,54	69,674	*	*	*	*	*	*	*	*	*	*
600	24"	609,6	5,54	83,763	6,35	95,881	*	*	*	*	*	*	*	*	*	*